

Product Specifications

ThermoTrace Infrared Laser Thermometer

Field of View	8:1 (85% energy collecting)
Measurement Range	-4°F to 626°F (-20°C to 330°C)
Display Range*	-67°F to 662°F (-55°C to 350°C)
Operating Range	32°F-122°F (0°C-50°C)
Accuracy	From -4°F to 32°F(-20°C to 0°C) ± 4°F (2°C); From 32°F to 626°F (-0°C to 330°C) ± 4°F (2°C) or 2% of reading, whichever is greater
Response Time	Less than 1 second
Display Hold Time	15 seconds
Display Resolution	0.1°F/0.1°C (switchable)
Emissivity Range	Factory set at 0.95 - adjustable 0.05 to 1.00 emissivity
Battery & Battery Life	AAA x 2pcs, 30 to 40 hour, auto power off after 15 seconds
Sighting Method	Non-coaxial laser
Weight	108 grams (3.8 oz) including batteries
Dimensions	1.02 in. x 1.77 in. x 5.04 in. (26mm x 45mm x 128mm)
IP Rating	IP54



Model 15036

- Waterproof
- Laser sighting
- Lightweight, sleek and compact
- Highly accurate
- Instant non-contact surface temperature measurement
- Useful with moving objects or for hard to reach places

* Extreme temperatures within the display range cannot be verified for accuracy



DeltaTrak manufactures products under an ISO 9000 registered quality management system

SS0027 13K1

