

# Product Specifications

## ThermoTrace Infrared Laser Thermometer

<b>Field of View</b>	8:1 (85% energy collecting)
<b>Measurement Range</b>	-4°F to 626°F (-20°C to 330°C)
<b>Display Range*</b>	-67°F to 662°F (-55°C to 350°C)
<b>Operating Range</b>	32°F-122°F (0°C-50°C)
<b>Accuracy</b>	From -4°F to 32°F(-20°C to 0°C) ± 4°F (2°C); From 32°F to 626°F (-0°C to 330°C) ± 4°F (2°C) or 2% of reading, whichever is greater
<b>Response Time</b>	Less than 1 second
<b>Display Hold Time</b>	15 seconds
<b>Display Resolution</b>	0.1°F/0.1°C (switchable)
<b>Emissivity Range</b>	Factory set at 0.95 - adjustable 0.05 to 1.00 emissivity
<b>Battery &amp; Battery Life</b>	AAA x 2pcs, 30 to 40 hour, auto power off after 15 seconds
<b>Sighting Method</b>	Non-coaxial laser
<b>Weight</b>	108 grams (3.8 oz) including batteries
<b>Dimensions</b>	1.02 in. x 1.77 in.x 5.04 in. (26mm x 45mm x 128mm)
<b>IP Rating</b>	IP54



### Model 15036

- Waterproof
- Laser sighting
- Lightweight, sleek and compact
- Highly accurate
- Instant non-contact surface temperature measurement
- Useful with moving objects or for hard to reach places

\* Extreme temperatures within the display range cannot be verified for accuracy



DeltaTrak manufactures products under an ISO 9000 registered quality management system

SS0027 13K1

