

AquaTuff™ 35132 Wrap&Stow



Model #: 35132

The AquaTuff™ 35132 model with DuraNeedle Wrap&Stow™ probe is the right choice when accuracy is your top priority. Total System Accuracy™ ensures this instrument and probe combination will provide high accuracy with temperature monitoring. This instrument/probe system delivers a TRUE $\pm 0.9^{\circ}$ accuracy and probes can be replaced in the field without the need for recalibration. The heavy-duty patented probe cable is reinforced with Kevlar® and a metal braid that neatly wraps and stows around the instrument.

DuraNeedle probes are best used for dense meats. They also work well with soft foods and liquids.

Product Specifications

Features	• Wrap & Stow probe included
Auto Off	Yes, after 10 minutes of non-use
Waterproof	Yes, IPX7
Includes	DuraNeedle probe Model 55032
Features	• Wrap & Stow probe included • Easy twist-open battery hatch
Calibration	Probe is calibrated with instrument for Total System Accuracy™
Features	• Wrap & Stow probe included • Easy twist-open battery hatch • Large, easy-to-read LCD screen • Probes can be easily replaced at your location without a need to re-calibrate
Certification	CE, RoHS, WEEE, & a NSF version is available
Warranty	5 Year Instrument Warranty, 1 Year Probe Warranty
F/C Switchable	Yes
Temperature Range	-100° to 500°F (-73° to 260°C)
Temperature Accuracy	$\pm 0.9^{\circ}$ ($\pm 0.5^{\circ}$) total system at ambient temperatures between 68° to 86°F (20° to 30°C)
Ambient Temperature Range	32° to 122°F (0° to 50°C)
Resolution	0.1°
LCD Height	.5" (12.7mm)
Housing Material	ABS plastic
Battery Type	(2) AAA
Battery Life	1800 hours
Weight	.45 lb (204 g) including batteries
Dimensions	7.125" x 2.75" x 1.3" (181mm x 70mm x 33mm)



877.782.2329