
AquaTuff™ 35135 Wrap&Stow



Model #: 35135

The AquaTuff™ 35135 series with Bell Surface Wrap&Stow™ probe is the right choice when accuracy is your top priority. The heavy-duty patented probe cable is reinforced with Kevlar® and a metal braid that neatly wraps and stows around the instrument.

The Bell Surface probe is best used for taking measurements of any flat surface. Bell self-orientates to a surface to give superior contact. Ideal for griddles and platens.

With any surface measurement, a small drop of oil or grease is recommended to aid in heat transfer to the bell sensor.

Download "Product Slick Sheet" in PDF form for more details.

Product Specifications

Certification	CE, RoHS, WEEE, NIST
Auto Off	Yes, after 10 minutes of non-use
Waterproof	Yes, IPX7
Warranty	5 Year Instrument Warranty, 1 Year Probe Warranty
Probes	Probes can be easily replaced at your location without a need to re-calibrate
F/C Switchable	Yes
Includes	Bell Surface probe Model 53035
Features	Wrap & Stow probe included + Easy twist-open battery hatch
Temperature Range	-100° to 500°F (-73° to 260°C)
Temperature Accuracy	+2.7°F & -6.3°F (+1.5°C & -3.5°C) on draft-free, flat, oiled surface in ambient temperatures between 68° to 86°F (20° to 30°C)
Ambient Temperature Range	32° to 122°F (0° to 50°C)
Resolution	0.1°
LCD Height	.5" (12.7 mm)
Housing Material	ABS
Battery Type	(2) AAA
Battery Life	1800 hours
Weight	.5 lb (227 g) including batteries
Dimensions	9.375" x 2.75" x 1.3" (238mm x 70mm x 33mm)



877.782.2329