

## AquaTuff™ 35232 Wrap&Stow



### Model #: 35232

The AquaTuff™ 35232 series with DuraNeedle Wrap&Stow™ probe is the right choice when accuracy is your top priority. Total System Accuracy™ ensures this instrument and probe combination will provide high accuracy with temperature monitoring. This instrument/probe system delivers a TRUE  $\pm 0.9^{\circ}$  accuracy and probes can be replaced in the field without the need for recalibration. The heavy-duty patented probe cable is reinforced with Kevlar® and a metal braid that neatly wraps and stows around the instrument.

DuraNeedle probes are best used for dense meats. They also work well with soft foods and liquids.

### Product Specifications

Waterproof	Yes, IPX7
Warranty	5 Year Instrument Warranty, 1 Year Probe Warranty
Certification	CE, RoHS, WEEE, NIST, & a NSF version is available
Auto Off	Yes, after 10 minutes of non-use or can be disabled
Calibration	Probe is calibrated with instrument for Total System Accuracy™
Includes	DuraNeedle probe Model 55032
LCD	Large, easy-to-read LCD screen
Battery Hatch	Easy twist-open battery hatch
Features	Hold Button will freeze current reading
LCD Backlight	Yes, LED backlight
F/C Switchable	Yes
Temperature Range	-100° to 500°F (-73° to 260°C)
Temperature Accuracy	$\pm 0.9^{\circ}$ ( $\pm 0.5^{\circ}$ ) total system at ambient between 68° to 86°F (20° to 30°C)
Ambient Temperature Range	32° to 122°F (0° to 50°C)
Resolution	0.1° / 1°, user selectable
LCD Height	.5" (12.7mm)
Housing Material	ABS
Battery Type	(2) AAA
Battery Life	1800 hours
Weight	.45 lb (204 g) including batteries
Dimensions	7.125" x 2.75" x 1.3" (181mm x 70mm x 33mm)



877.782.2329