

AquaTuff™ 35235 Wrap&Stow



Model #: 35235

The AquaTuff™ 35235 series with Bell Surface Wrap&Stow™ probe is the right choice when accuracy is your top priority. The heavy-duty patented probe cable is reinforced with Kevlar® and a metal braid that neatly wraps and stows around the instrument.

The Bell Surface probe is best used for taking measurements of any flat surface. Bell self-ori-ents to a surface to give superior contact. Ideal for griddles and platens.

With any surface measure, a small drop of oil or grease is recommended to aid in heat transfer to the bell sensor.

Download "Product Slick Sheet" in PDF form for more details.

Product Specifications

LCD	Large, easy-to-read LCD screen
Auto Off	Yes, after 10 minutes of non-use or can be disabled
Waterproof	IPX7
Certification	CE, RoHS, NIST, & WEEE
F/C Switchable	Yes
LCD Backlight	Yes, LED backlight
Includes	Bell Surface probe Model 55035
Features	• Hold Button will freeze current reading
Warranty	5 Year Instrument Warranty, 1 Year Probe Warranty
Battery Hatch	Easy twist-open battery hatch
Temperature Range	-100° to 500°F (-73° to 260°C)
Temperature Accuracy	+2.7°F & -6.3°F (+1.5°C & -3.5°C) on draft-free, flat, oiled surface in ambient temperatures between 68° to 86°F (20° to 30°C)
Ambient Temperature Range	32° to 122°F (0° to 50°C)
Resolution	0.1° / 1°, user selectable
LCD Height	.5" (12.7 mm)
Housing Material	ABS
Battery Type	(2) AAA
Battery Life	1800 hours
Weight	.5 lb (227 g) including batteries
Dimensions	9.375" x 2.75" x 1.3" (238mm x 70mm x 33mm)



877.782.2329