

# AquaTuff™ 35235 Wrap&Stow



## Model #: 35235

The AquaTuff™ 35235 series with Bell Surface Wrap&Stow™ probe is the right choice when accuracy is your top priority. The heavy-duty patented probe cable is reinforced with Kevlar® and a metal braid that neatly wraps and stows around the instrument.

The Bell Surface probe is best used for taking measurements of any flat surface. Bell self-ori-ents to a surface to give superior contact. Ideal for griddles and platens.

With any surface measure, a small drop of oil or grease is recommended to aid in heat transfer to the bell sensor.

Download "Product Slick Sheet" in PDF form for more details.

## Product Specifications

LCD	Large, easy-to-read LCD screen
Auto Off	Yes, after 10 minutes of non-use or can be disabled
Waterproof	IPX7
Certification	CE, RoHS, NIST, & WEEE
F/C Switchable	Yes
LCD Backlight	Yes, LED backlight
Includes	Bell Surface probe Model 55035
Features	• Hold Button will freeze current reading
Warranty	5 Year Instrument Warranty, 1 Year Probe Warranty
Battery Hatch	Easy twist-open battery hatch
Temperature Range	-100° to 500°F (-73° to 260°C)
Temperature Accuracy	+2.7°F & -6.3°F (+1.5°C & -3.5°C) on draft-free, flat, oiled surface in ambient temperatures between 68° to 86°F (20° to 30°C)
Ambient Temperature Range	32° to 122°F (0° to 50°C)
Resolution	0.1° / 1°, user selectable
LCD Height	.5" (12.7 mm)
Housing Material	ABS
Battery Type	(2) AAA
Battery Life	1800 hours
Weight	.5 lb (227 g) including batteries
Dimensions	9.375" x 2.75" x 1.3" (238mm x 70mm x 33mm)



877.782.2329