



Jumbo Display Wall Mount Thermo-Hygrometer 13309



- Internal temperature and humidity sensors
- External temperature probe
- Probe holder with self-adhesive backing
- °C/°F selectable
- Jumbo display for temperature and humidity
- Alarm clock and hourly chime
- Min/Max memory - lowest and highest readings stored for instant recall

SPECIFICATIONS MODEL 13307	
Temperature Range Internal	14°F to 122°F (0°C to 50°C)
Temperature Range External Probe	-58°F to 158°F (-50°C to 70°C)
Humidity Range Internal	10% to 99%
Temperature Accuracy (Int. & Ext.)	±1.8°F (1°C) from 32°F to 104°F (0°C to 40°C)
Humidity Accuracy (Internal)	±5% R.H. from 40% to 70% R.H. at 77°F~86°F (25°C~30°C)
External Temperature Sensor	Cable length: 6.56 ft/2 meters; probe: 20mm (L) x 4mm Diameter
Resolution	R.H.1%, temperature 0.1°F /0.1°C
Display Reading Update	10 Seconds
Display Window Size	3.5 in. (W) x 2.36 in. (H) (80 mm x 60 mm)
Product Size	3.74 in. x 4.02 in. x .75 in.(95 mm x 102 mm x 19 mm)
Weight	4.8 oz. (118.4 g)
Body Casing	Polycarbonate and ABS plastic
Sensor Type Temperature	thermistor
Sensor Type Humidity	electronic resistive



PTC Metrology™ is accredited by A2LA for temperature calibration to ISO/IEC 17025 Certifications are NIST traceable. Visit our website www.ptc1.com to see our services and copies of our A2LA Certificate and Scope.

Model [13309](#) is available with a NIST Certification which includes 1 point humidity & 1 point temperature.